

CH1212 / CH2212

Automatic Float Battery Charger

12 VDC 15 Amp Low Ripple

Features

- Adjustable for Lead Acid or Lead Calcium Batteries
- Float Charge Factory Set For Lead Acid Batteries, Charger Will Supply Current Until Battery Voltage is Equal To Set Voltage
- Reverse polarity protected
- Current Limiting Protection



Specifications

AC Input Power	CH1212	Single Phase 110 VAC $\pm 10\%$
	CH2212	Single Phase 220 VAC $\pm 10\%$
	Frequency	50/60 Hz
Float Charge Voltage		13.8 VDC
Output Current		Max. 15 ADC
Power Input Fuse		10 Amp / 250 VAC
Unit Power Dissipation		Max. 345 watt

Protection	Reverse polarity, over-voltage, short circuit, current limiting
Storage Temperature	-20~40 °C
Relative Humidity	Maximum 90%
Dimensions	293.0 (L) x 157.0 (W) x 185.0 (H) mm
Weight	9.2 Kg $\pm 2\%$



CH1224 / CH2224

Automatic Float Battery Charger

24 VDC 15 Amp Low Ripple

Features

- Adjustable for Lead Acid or Lead Calcium Batteries
- Float Charge Factory Set For Lead Acid Batteries, Charger Will Supply Current Until Battery Voltage is Equal To Set Voltage
- Reverse polarity protected
- Current Limiting Protection

Specifications

AC Input Power	CH1224	Single Phase 110 VAC $\pm 10\%$
	CH2224	Single Phase 220 VAC $\pm 10\%$
	Frequency	50/60 Hz
Float Charge Voltage		27.6 VDC
Output Current		Max. 15 ADC
Power Input Fuse		10 Amp / 250 VAC
Unit Power Dissipation		Max. 525 watt

Protection	Reverse polarity, over-voltage, short circuit, current limiting
Storage Temperature	-20~40 °C
Relative Humidity	Maximum 90%
Dimensions	293.0 (L) x 157.0 (W) x 185.0 (H) mm
Weight	10.2 Kg $\pm 2\%$



固也泰電子工業有限公司
KUTAI ELECTRONICS INDUSTRY CO., LTD.



TEL: +886-7-8121771 FAX: +886-7-8121775
Head Office: No.3, Lane 201, Chien Fu St., Chyan Jenn Dist., Kaohsiung, TAIWAN
Please link to <http://www.kutai.com.tw> for detailed manual.