

電源自動切替スイッチ (ATS) スペック表

| ATS 型番 | 定格電流(A) 周囲温度 40°C | | | | | | 交流定格遮断容量 (KA) IEC 60947-2 Icu/Ics | | | | |
|------------|----------------------|-----|------|------|------|------|--------------------------------------|------|------|------|------|
| | | | | | | | 240V | 380V | 415V | 440V | 550V |
| ATS3BC0100 | 30 | 40 | 50 | 60 | 75 | 100 | 25 | 18 | 18 | 15 | 10 |
| ATS4BC0100 | 30 | 40 | 50 | 60 | 75 | 100 | 25 | 18 | 18 | 15 | 10 |
| ATS3BC0250 | 125 | 150 | 175 | 200 | 225 | 250 | 50 | 30 | 30 | 25 | 20 |
| ATS4BC0250 | 125 | 150 | 175 | 200 | 225 | 250 | 50 | 30 | 30 | 25 | 20 |
| ATS3BC0400 | 250 | 300 | 350 | 400 | | | 50 | 30 | 30 | 25 | 20 |
| ATS4BC0400 | 250 | 300 | 350 | 400 | | | 50 | 30 | 30 | 25 | 20 |
| ATS3BC0600 | 500 | 600 | | | | | 50 | 30 | 30 | 25 | 20 |
| ATS4BC0600 | 500 | 600 | | | | | 50 | 30 | 30 | 25 | 20 |
| ATS3BC0800 | 700 | 800 | | | | | 50 | 30 | 30 | 25 | 20 |
| ATS4BC0800 | 700 | 800 | | | | | 50 | 30 | 30 | 25 | 20 |
| ATS3BC1000 | 500 | 600 | 700 | 800 | 900 | 1000 | 85 | 50 | 50 | 50 | 30 |
| ATS4BC1000 | 500 | 600 | 700 | 800 | 900 | 1000 | 85 | 50 | 50 | 50 | 30 |
| ATS3BC1200 | 600 | 700 | 800 | 1000 | 1200 | | 85 | 50 | 50 | 50 | 30 |
| ATS4BC1200 | 600 | 700 | 800 | 1000 | 1200 | | 85 | 50 | 50 | 50 | 30 |
| ATS3BC1600 | 800 | 900 | 1000 | 1200 | 1400 | 1600 | 100 | 65 | 65 | 50 | 35 |
| ATS4BC1600 | 800 | 900 | 1000 | 1200 | 1400 | 1600 | 100 | 65 | 65 | 50 | 35 |