

Basic Transfer Switch (BTS) Selection Chart

BTS Part Number	Rated Current(A) Ambient Temperature 40 °C						AC Rated Breaking Capacity (KA) IEC 60947-2 Icu/lcs				
							240V	380V	415V	440V	550V
BTS3BE0100	30	40	50	60	75	100	25	18	18	15	10
BTS4BE0100	30	40	50	60	75	100	25	18	18	15	10
BTS3BE0225	125	150	175	200	225		50	30	30	25	20
BTS4BE0225	125	150	175	200	225		50	30	30	25	20
BTS3BE0400	250	300	350	400			50	30	30	25	20
BTS4BE0400	250	300	350	400			50	30	30	25	20
BTS3BE0600	500	600					50	30	30	25	22
BTS4BE0600	500	600					50	30	30	25	22
BTS3BE0800	700	800					50	30	30	25	22
BTS4BE0800	700	800					50	30	30	25	22
BTS3BE1000	500	600	700	800	900	1000	85	50	50	50	42
BTS4BE1000	500	600	700	800	900	1000	85	50	50	50	42
BTS3BE1200	600	700	800	1000	1200		85	50	50	50	42
BTS4BE1200	600	700	800	1000	1200		85	50	50	50	42
BTS3BE1600	800	900	1000	1200	1400	1600	100	65	65	65	50
BTS4BE1600	800	900	1000	1200	1400	1600	100	65	65	65	50