

Kutai Remote Communication Module Comparison List

Model Name	KCU-01	KCU-02	KCU-03	KCU-04
Product Illustration				
Hardware	USB	RS485	Ethernet	Can Bus
Connector / Cable	Mini USB / USB cable	Euroblock / Twisted-Pair (Belden)	RJ-45 plug	Euroblock / Twisted-Pair (Belden)
Address Mode	N/A	Through controller	Fixed IP	N/A
Smart Phone	N/A	N/A	Available	N/A
Product Features	- Friendly software interface, for configuration and monitoring - Support USB modem for remote communication - Support mini USB/5P B-type cable - Equipped with LED status indicator	- Friendly software interface, for configuration and monitoring - Working under Half-Duplex mode - Automatic configuration of RS485 address and baud rate - Equipped with LED status indicator	- Friendly software interface, for configuration and monitoring - All transfer data with encrypted and decrypted protection - System automatically disconnect after 3 failure registry logins - System automatically disconnect if data packet is not correctly received within 5 second after registry login - Server Device, supports maximum of 4 users to simultaneously login - Security password to enable controller system parameter configuration - Equipped with LED status indicator - Support 10-Base-T network transmission	- Supports and decodes CAN Bus SAE-J1939 protocol to provide controller with necessary sensing information - Replace coolant temperature, oil pressure, engine speed(MPU) sensor - Provide warning message - Equipped with LED status indicator - J1939 Decode - Warning Message: Over Speed, Low Speed, Low oil pressure, High coolant temperature, Low fuel level, Low Battery Voltage and Other, Warning Message, Once Per Second
Related Products	 ATS-22 ATS-33 ATS-34 GCU-100 AMF-10 GCU-3000			
Dimension (LxWxH)	35.0 x 23.0 x 65.0 mm	35.0 x 23.0 x 65.0 mm	35.0 x 23.0 x 65.0 mm	35.0 x 23.0 x 65.0 mm
Weight	27.6 g +/- 2%	27.8 g +/- 2%	31.0 g +/- 2%	27.6 g +/- 2%

Model Name	KCU-30	KCU-40	KCU-50	KCU-60
Product Illustration				
Hardwar	Ethernet	WIFI module	SIM card module	Re-program module
Connector / Cable	RJ-45 plug	N/A	N/A	N/A
Address Mode	Dynamic IP	Dynamic IP	Dynamic IP	N/A
Smart Phone	Available	Available	N/A	N/A
Product Features				
Related Products				
Dimension (LxWxH)				
Weight				