CH1712 / CH1724

Wall Mountable Automatic Battery Charger 20Amp

Features

- Low ripple voltage (below +/-3%)
- Float / equalize charge mode
- Adjustable equalize charging time
- Voltage detector and over voltage protection
- No current drain when input power is off
- Set any charge current up to 20Amp with over current protection
- Selectable 110/220Vac input




Specifications	
Power Input	Float Charge Voltage Range
Voltage 110/220 Vac +/-10% 1 phase (selectable)	12 Vdc 13.0 to 14.5 Vdc (adjustable)
Frequency 50/60 Hz +/-5%	24 Vdc 25.8 to 28.0 Vdc (adjustable)
Equalize Charge Output Voltage	Protection Short circuit, over current, charge fail alarm, over voltage,
CH1712 Charge 12 Vdc battery at 14.5 Vdc	no current drain when input power is off
CH1724 Charge 24 Vdc battery at 28.8 Vdc	Output Current Range 0.5 to 20.0 Adc
Float Charge Output Voltage	Voltage Regulation Less than +/-1%
CH1712 Charge 12 Vdc battery at 13.8 Vdc	Equalize Charging Time 6, 12, 24 hours setting
CH1724 Charge 24 Vdc battery at 27.6 Vdc	Charge Mode Float charge and equalize charge
Equalize Charge Voltage Range	Cooling Forced fan cooling
12 Vdc 13.5 to 16.0 Vdc (adjustable)	Efficiency More than 80% @ full load
24 Vdc 27.0 to 31.0 Vdc (adjustable)	Ripple +/-3%

Front View and Illustrations

- DC Voltage Meter
- DC Current Meter
- Power LED

- Equalize Charge LED
- Float Charge LED
- Equalize Charge Setting Button
- Adjustable Equalize Voltage
- Adjustable Float Charge Current
- Adjustable Charge Voltage

Dimensions



Environment

-20 to +60 °C **Operating Temperature** Storage Temperature -20 to +40 °C **Relative Humidity** Max. 90%

Physical Specifications

Dimensions	400.0 (L) x 300.0 (W) x 255.0 (H) mm
Weight	CH1712 24.6 Kg +/-2%
	CH1724 30.0 Kg +/-2%

Input Power MCCB

Output Power MCCB



TEL: +886-7-8121771 FAX: +886-7-8121775 Website: www.kutai.com.tw Headquarters: No.3, Ln. 201, Qianfu St., Qianzhen Dist., Kaohsiung City 80664, Taiwan

